



TEKNİK ÖZELLİKLER	KM-80	KM-100	KM-150	KM-200
<b>HAREKETLER</b>				
X EKSENİ	800 mm	1000 mm	1500 mm	2000 mm
Y EKSENİ	400 mm	500 mm	650 mm	850 mm
Z EKSENİ	450 mm	530 mm	620 mm	710 mm
İŞ MİLİ KOLON ARASI MESAFE	400 mm	500 mm	630 mm	870 mm
İŞ MİLİ BURNU İLE TABLA YÜZEYİ	100 ~ 550 mm	100 ~ 630 mm	100 ~ 720 mm	100 ~ 810 mm
<b>TABLA ÖZELLİKLERİ</b>				
TABLA BOYUTLARI	1270 x 355 mm	1370 x 406 mm	1800 x 450 mm	2180 x 810 mm
MAKSİMUM PARÇA AĞIRLIĞI	500 kg	600 kg	1000 kg	1800 kg
T SLOT ÖLÇÜLERİ	16 / 3T	16 / 3T	16 / 5T	18 / 5T
<b>İŞ MİLİ</b>				
İŞ MİLİ DEVRİ	8000 / 10000 dev/dak	8000 / 10000 dev/dak	8000 / 10000 dev/dak	8000 / 10000 dev/dak
İŞ MİLİ KONIĞI	BT#40	BT#40	BT#40	BT#40
İŞ MİLİ MOTOR GÜCÜ	7,5 HP	10 HP	15 HP	20 HP
<b>EKSENLER</b>				
EKSEN MOTOR GÜCÜ (X / Y / Z)	1,5 kW	2 kW	2 kW	3,5 kW
HIZLI HAREKET / G0 (X / Y / Z)	8 m/dak (ops. 20m/dak)	8 m/dak (ops. 20m/dak)	8 m/dak (ops. 20m/dak)	8 m/dak (ops. 20m/dak)
MAX. KESME HIZI / G1 (X / Y / Z)	8 m/dak	8 m/dak	8 m/dak	8 m/dak
<b>DİĞER ÖZELLİKLER</b>				
GEREKLİ GÜÇ İHTİYACI	15 kVA	15 kVA	20 kVA	30 kVA
MAKİNA AĞIRLIĞI	3 ton	3,5 ton	4,5 ton	7 ton
EN X DERİNLİK	2100 x 1950 mm	2280 x 2080 mm	3000 x 2280 mm	3000 x 2280 mm
YÜKSEKLİK	2200 mm	2200 mm	2550 mm	2550 mm



**SYNTEC**



**MITSUBISHI**

**EKONOMİK**

